



## TECHNICAL DATA SHEET

# Butyl Mastic Sealant



### Benefits

Excellent adhesion  
Excellent flexibility  
Excellent water resistance  
Excellent pumpability and gunnability  
Non-corrosive to metals  
UV resistant

### Description

izolet mastic sealant is one component, flexible, non-hardening, non-drying, non-oxidizing butyl elastomer sealant with excellent adhesion to most common substrates.

### Seals and Bonds

- ✓ Variety of metals
- ✓ Wood
- ✓ Glass
- ✓ Concrete
- ✓ Asphalt
- ✓ Plastic
- ✓ Gypsum
- ✓ Foam boards
- ✓ Masonry surfaces

### Uses

- ✓ Curtainwall joints
- ✓ Ribbed roof panels
- ✓ Metal finishes
- ✓ Precast construction
- ✓ Roofs, gutters and downspouts
- ✓ Heating and air conditioning ducts
- ✓ Secondary glazing
- ✓ Acoustical sealant
- ✓ Vapor barrier
- ✓ Fixing and isolating kitchen and vanity tops, bathtubs and sinks

### Colors

Black, Gray, Off-White

### Packaging

Available 300 ml cartridges  
20 Lt Pails (upon request)  
200 Lt Drums (upon request)

#### TYPICAL PHYSICAL PROPERTIES

Tack Free Time	Permanently Tacky
Specific Gravity	1.57 ± 0.07
Service Temperature	-50 °C to 100 °C
Application Temperature	-20 °C to 50 °C
Water and Chemical Resistance	Excellent
Colors	Black, Grey and Off-White

\* Custom products are available

www.izolet.com - info@izolet.com  
Alemdağ Cad. Site Yolu Ak Sanayi Sitesi 2. Kısım A Blok No:25  
34768 Ümraniye / İstanbul / TURKEY  
Phone : +90 (216) 533 24 24